



# International Journal of Advanced Academic Studies

E-ISSN: 2706-8927  
P-ISSN: 2706-8919  
Impact Factor (RJIF): 7.28  
[www.allstudyjournal.com](http://www.allstudyjournal.com)  
IJAAS 2026; 8(1): 42-45  
Received: 25-10-2025  
Accepted: 27-11-2025

**Shivani Agrahari**  
Research Scholar, Department  
of Zoology, Govt. Model  
Science College, Rewa,  
Madhya Pradesh, India

**Vinita R Kashyap**  
Associate Professor,  
Department of Zoology, Govt.  
Model Science College, Rewa,  
Madhya Pradesh, India

## Comparative assessment of physico-chemical characteristics to underground and surface water Mauganj (M.P.) India

**Shivani Agrahari and Vinita R Kashyap**

**DOI:** <https://www.doi.org/10.33545/27068919.2026.v8.i1a.1809>

### Abstract

The present study deals with the comparative assessment of the Physicochemical characteristics of underground and surface water (Pond) of the Mauganj District, Madhya Pradesh. Different physicochemical parameters (TDS, pH, Iron, Total hardness, Alkalinity, Chloride, Calcium, Arsenic, and Magnesium) were determined during the month of March to analyze and compare the underground water and Surface water (Pond) quality. Collected samples were analyzed according to APHA (2005) for different physicochemical parameters, and the results were compared with standard values prescribed by ISI-IS: 2296 and BIS (1991). The study revealed that the Iron level was much lower in pond water compared to the underground water, which is much above the Desirable or permissible limits. The TDS of pond water is much lower than Handpump water. The total hardness of pond water was much lower than underground water. The alkalinity of pond water was found to be between 100-160 mg/l. Whereas the alkalinity of underground water ranged from 240-360 mg/l.

**Keywords:** Arsenic, assessment, calcium, iron, underground water

### Introduction

Our earth contains about  $1.36 \times 10$  cubic kilometers of water; of this, about 97% is contained in oceans and seas, about 2% is locked in glaciers and polar ice, and the rest (about 1%) is in lakes, streams, rivers, and underground recourse. The sea (ocean water & salty) and is not useful for human consumption. Less than 1% of water is effectively available as freshwater, Suitable for human consumption and several activities like agriculture, fishing, recreation, etc.

Ponds have been used since time immemorial as a traditional source of water supply in India (Mahobe 2013) <sup>[15]</sup>. A pond is also important for ecology as it has much significance in the environment- as it supports aquatic biodiversity, has large carbon sequestration capacity, regulates temperature and humidity (microclimate, regulation); rainwater harvesting & surface groundwater recharge other beneficial effects such as aquaculture (Kumar and Pratap 2015) <sup>[11]</sup>. Ponds are fragile ecosystems and are venerable to pollution (Bassi *et al.*, 2014) <sup>[2]</sup>. There are various sources of contamination in these ponds (Swarnakar and Choubey 2016) <sup>[26]</sup>. However, the pond is polluted mainly due to the discharge of wastewater from nearby areas (Bhulyan and Gupta 2007) <sup>[4]</sup>. Pollution primarily affects physicochemical characteristics leading to the destruction of the community, disrupting delicate food webs, and deteriorating the lake's environment (Golder and Chattopadhyay 2016) <sup>[8]</sup>. The physicochemical properties of water contribute to decision-making for pollution control in the environment protection process (Kamal *et al.*, 2007, Verma *et al.*, 2012; Patel and Parikh, 2013, Uddin *et al.*, 2016.) <sup>[10, 29, 19]</sup>.

Mauganj is the 53rd district of Madhya Pradesh, carved out from the Rewa district in 2023 and serving as the administrative headquarters for its namesake town. It is the 5th district in the Rewa division, with an area of 1866.88 sq km, and is known for its religious sites and scenic waterfalls. The district comprises three tehsils-Mauganj, Hanumana, and Naigarhi and shares borders with Uttar Pradesh. Mauganj district's geographical location is approximately at 24.68°N latitude and 81.88°E longitude. It is situated in the state of Madhya Pradesh, India, with an average elevation of about 313 meters (1,026 feet) above sea level. These rivers fed perennial ponds, while some ponds were seasonal and dry during the summer

**Corresponding Author:**  
**Shivani Agrahari**  
Research Scholar, Department  
of Zoology, Govt. Model  
Science College, Rewa,  
Madhya Pradesh, India

season; when the underground water level fell to pollution, eutrophication and urbanization, many ponds lost their status, and now only scares no. of ponds can be seen here. A number of workers have done their work on physico-chemical parameters of pond water (Paul and Mukerjee 2006, Chaurasia and Pandey 2007, Kiran 2010, Mondal *et al.*, 2011, Prasath *et al.*, 2013, Mahobe 2013, Bharviman and Puttaiah 2014, Mishra *et al.*, 2014, Swarnakar and Choubey 2016, Kumari and singh 2016) [21, 5, 9, 16, 23, 15, 26, 12]. A literature review suggested that a systematic study on the comparative study of water quality of underground and pond water of Mauganj has not been done. In this regard present study aimed to investigate a comparative account of the Physico-chemical properties of water in terms of certain selected parameters. The principal objective was to investigate the fluctuation of Physicochemical parameters of pond water and underground amber of Mauganj. In this way, the present study will generate an important baseless database for the pond water over underground water, which would be helpful to evaluate the difference in water quality of both ponds and underground water.

## Materials and Methods

### Study area

The study was carried out in the 3 ponds and handpump in three random Mauganj places.

**Gorama dam:** It is located in Hanumna tehsil of Mauganj district in Madhya Pradesh, and falls under the Bijholi Shuklan village panchayat.

**Atarital Dam:** Studies on fish communities have been conducted at the Atarital Dam in Mauganj, indicating it is another significant water body in the district.

**Kanhaiya dam:**

### Collection of water sample

A total number of 18 samples were collected for analysis from three random ponds and hand pumps located in Mauganj. Water samples were collected and stored in 1 litre and 0.5-litre capacity clean with high-density polythene bottles with poly seal caps. Before collecting samples, bottles were properly washed and rinsed with the water to be sampled. The hand pumps were pumped for a sufficient duration before collecting the underground water sample so that the stagnant water, if any, was completely removed. The dam water sample was taken from the bank of the dam. 1-litre bottle 6 samples were used for physico chemical assessment of TDS, pH, Total hardness, Alkalinity, Chloride, Calcium, and Magnesium.

A 0.5-litre bottle of 6 samples was used for the physico-chemical assessment of only Iron and Arsenic, and sampling was thoroughly washed and rinsed with 8N HNO<sub>3</sub>, followed- by distilled water—the 5 ml conc. HNO<sub>3</sub> per half a litre of the sample was added at the time of collection to minimize the adsorption of metals on the container walls and to check bacterial growth.

A small vial of 25 ml was used to ascertain the bacteriological quality of water.

Bacteriological field test kit, which works on the H<sub>2</sub>S strip method. This method is a rapid and reliable method which is used to assess microbial water quality. For assessment, opened the kit cap and filled the water sample of both 3 ponds and 3 handpumps up to the fill line (20 ml). Replaced

the cap and shook gently. Placed the bottle on a flat surface at room temperature for 24-48 hours and observed the results. If the water sample changes colour, turning black, it is contaminated.

**Methods:** There were 6 sampling spots selected through random sampling in the Mauganj district, including dam water from Gorama, Atarital dam and Kanhaiya dam. Handpump water from Naigarhi block near busstand, Hanumana block near hospital and Mauganj block near block office. The water sample was collected in the month of March, which can be called the pre-monsoon period when groundwater contained heavy metals in higher concentration compared to the post-monsoon period. The collected samples were submitted to PHED (Public Health Engineering Department) Mauganj, Government of Madhya Pradesh, for estimation of the physico chemical test of groundwater.

## Results and Discussion

### Total Alkalinity

Alkalinity expresses the water's buffering capacity, which appreciably maintains the pH by absorbing excess H<sup>+</sup> ions and protecting the water body from pH fluctuation. The main factors for alkalinity are carbonates, bicarbonates, hydroxide ions, ammonia, organic acid, etc. Alkalinity acts as a buffer against rapid pH change (Lodh *et al.*, 2014; Paul *et al.*) [13]. Alkalinity is recorded within the prescribed range given by WHO, i.e. 200-600 mg/l, whereas the mean value of pond water is 160 mg/l, whereas the mean value of handpump water was 313.33 mg/l. Mondal *et al.*, 2011<sup>[16]</sup> also observed a similar result for pond water. Alkalinity showed a significant, positive correlation with hardness.

### Chloride

Chloride occurs naturally in all types of water. In natural freshwater, however, its concentration of chloride increases the corrosive property of water. The chloride content of studied water samples was within the permissible limit prescribed by BIS as the maximum value of chloride in Hand Pump water was 60 mg/l, and that of pond water was 40 mg/l. similar results were also observed by Verma *et al.*, 2010<sup>[28]</sup>. Qureshimatva *et al.*, 2015<sup>[24]</sup>; Paul DK and Sumona Sanyal *et al.*, 2017<sup>[22]</sup>. The observed value of chloride is within the desirable value, i.e. 250 mg/l as per BIS standards (IS 10500:1991).

### Total Dissolved Solids (TDS)

Solids refer to the suspended and dissolved matter in water (Qureshimatva). It is a very useful parameter describing the chemical constituents of the water and can be considered as edaphically relation that contributes to productivity within the body (Goher 2002)<sup>[7]</sup>. The mean TDS of handpump is 340 mg/l. Whereas the Mean TDS of pond water is 169.66 mg/l. Both pond water and underground water were under desirable limit Type and quality of TDS define the color and electrical conductivity of the water body (Tank and Chippa 2013)<sup>[27]</sup>.

### Total Hardness (TH)

Total hardness is caused due to the presence of cations etc. This like Ca<sup>++</sup>, Mg<sup>++</sup>, Fe<sup>++</sup> etc. This is the property of water to precipitate soap by forming the complex with calcium and magnesium present in water. TH of the studied

pond and the handpump was found within the prescribed limit, and the Mean value recorded was 313.33 mg/l of handpump, whereas the Mean TH of pond water was found to be 160 mg/l. Patil and Tijara 2001, have observed similar results in pond water.

### pH

One important factor that serves as an index for pollution is pH (Moundiotiya *et al.* 2004)<sup>[17]</sup>. PH is the indicator of the acidic or alkaline condition of water status. The standard for any purpose in terms of pH is 6.5-8.5. A 95% confidence limit for pH was found to be 7.78 to 8.26. It shows the alkaline nature of water. Waxi and Subla (1990) reported that the pH value was above 8 in natural water. The pH of the studied pond water and hand pump water was found to be within the prescribed limit of 7.10 7.84.

### Calcium (Ca)

Calcium is important for the proper development of bones and teeth of human beings. The hand pump water contains calcium in different ranges from 64 -168 mg/l, whereas pond water contains calcium in the range of water 30-40 mg/l. The calcium level in both the water was sample found within the permissible limit.

### Magnesium (Mg)

High Mg level in drinking water reduces the risk of death from Ischemic Heart disease, especially in men (Ragna Rylander, MD *et al.*, 1991)<sup>[25]</sup>. Magnesium is important for many processes in the body, including regulating muscle and nerve function, blood sugar levels, blood pressure, making protein, bone and DNA. The magnesium level of both pond and handpumps water was found within the permissible limit of 30 to 100 mg/l. The pond water was found within the range of 16 to 17.28 mg/l, while the hand pump water was found within the range of 21-60 mg/l.

### Arsenic (As)

Arsenic is the most toxic heavy metal found in water. Arsenic at high concentrations coagulates protein, possibly attacking the Sulphur bonds and maintaining the secondary and tertiary structures of proteins.

The three major biochemical actions of Arsenic are

coagulation of proteins, complexation with Coenzymes, and uncoupling of phosphorylation. Acute Arsenic poisoning arises from ingesting as little as 0.01 mg/l of As. Chronic effects can appear from its accumulation in the body at low intake levels for prolonged periods. Arsenic occurs in water as a result of industrial mineral dissolution, discharges, or the application of insecticides. The arsenic level of both pond and hand pump water was found within a desirable limit of 0.01 mg/l. Pond water contained Arsenic levels from the range of 0.002 to 0.004 mg/l. At the same time, hand pump water contained Arsenic levels in the range of 0.001 to 0.003 mg/l.

### Iron (Fe)

Pryuttma & Abhay Prakash / IJAP, 10(2), 16-20, 2023 Iron is a mineral that the body needs for growth and development. Our body uses iron to make Hemoglobin, a protein in red blood cells that carries oxygen from the lungs to all body parts (National Institutes of Health Office of Dietary Supplements). Surface water generally contains less than 1 ppm of Fe. Some groundwaters and acid surface drainage may water contain much higher levels of Fe, more than 2 ppm contain much and es staining of clothes (while washing), and porcelain imparts a bitter, astringent taste. The permissible limit for filterable Fe in drinking water is 0.3ppm, or Hand pump water contains a permissible limit from above the range of 1.40 to 1.80 mg/l. While pond water permissible contains limited iron in the 0.57 to 0.82 mg/l below. Range of Iron is a mineral that the body needs for growth and development. Our body uses iron to make Hemoglobin, a protein in red blood cells that carries oxygen from the lungs to all body parts (National Institutes of Health Office of Dietary Supplements). Surface water generally contains less than 1 ppm of Fe. Some groundwaters and acid surface water drainage contain much higher levels of Fe. Water containing more than 2 ppm Fe causes staining of clothes (while washing) and porcelain and imparts a bitter, astringent taste. The permissible limit for filterable Fe in drinking water is 0.3 ppm or 1.00 mg/l. Hand pump water contains Iron much above the permissible limit in the range of 1.40 to 1.80 mg/l. While pond water permissible limit contains Iron below the permissible limit in the range of 0.57 to 0.82 mg/l.

**Table 1:** Physico-Chemical Test Report

S. No.	Block	Panchyat	Location details	TDS (mg/L)	pH	Iron (mg/L)	Total hardness (mg/L)	Alkalinity	Chloride	Ca	Mg	Ar
<b>Desirable Limit</b>				<b>500</b>	<b>6.5</b>	<b>1.00</b>	<b>200</b>	<b>200</b>	<b>250</b>	<b>75</b>	<b>30</b>	<b>0.01</b>
Permissible limit in the absence of alternate source				2000	8.5	NR	600	600	1000	200	100	NR
1.	Hanumana		Gorama dam	143	7.20	0.82	120	100	40	48	16.8	0.004
2.	Mauganj		Atarital dam	148	7.10	0.57	180	140	40	48	17.28	0.002
3.	Mauganj		Kanhaiya dam	218	6.82	0.75	180	160	30	48	16	0.002
4.	Hanumana		Handpump	380	7.72	1.40	340	300	60	160	57.6	0.001
5.	Naigarhi		Handpump	340	7.54	1.80	320	300	60	168	60	0.003
6.	Maujganj		Handpump	300	7.32	1.42	280	260	40	64	21	0.001

### Conclusion

The present study provides a comparative account of physico-chemical parameters; along with it, the study provides baseline data for the conservation and monitoring of ponds in Khagaria. From the above discussion, it was observed that physico-chemical parameters such as TDS, pH, Total Hardness, Alkalinity, Chloride, Calcium, Magnesium and Arsenic, Iron content in the pond are found

within the permissible limit, while handpump water contained iron above the permissible limit. Handpump water did not contain Bacterial residue, while pond water contained Bacteria. No. of Bacteria was more near the bank of the pond, which was not in use high iron in water content leads to an overload, which can cause diabetes hemochromatosis, stomach problems, and nausea. It can also damage the liver, pancreas, and heart. Excess quantities

in water can harm skin cells, leading to infection and wrinkles. Moreover, such water does not rinse off the body's soap residue, causing clogged skin pores and build up of oil in the skin, resulting in many skin problems such as eczema or acne (Peninsula water conditioning Delmarva's problem water expert).

The study revealed that pond water and hand pump water is unfit for human consumption; if not filtered properly, pond water contains Bacteria and hand pump contains iron. Both pond water and handpump water can be used for aquaculture, irrigation and recreational purpose.

**Acknowledgement:** Authors are highly thankful to authority of Govt. Model Science College, Rewa (M.P.) for granting permission and carryout the work.

## References

1. American Public Health Association. Standard methods for the examination of water and wastewater. 21st ed. Eaton AD, Franson MAH, editors. USA; 2005.
2. Bassi N, *et al.* Status of wetlands in India: A review of extent, ecosystem benefits, threats and management strategies. *Journal of Hydrology: Regional Studies.* 2014;2:1-19.
3. Bureau of Indian Standards. Indian standards for drinking water. New Delhi: Bureau of Indian Standards; 1991. IS 10500.
4. Bhuiyan JR, Gupta S. A comparative hydrobiological study of a few ponds of Barak Valley, Assam and their role as sustainable water resource. *Journal of Environmental Biology.* 2007;28(4):799-802.
5. Chaurasia M, Pandey GC. Study of physico-chemical characteristics of the pond of Ayodhya-Faizabad. *Indian Journal of Environmental Protection.* 2007;27(11):1019-1023.
6. Hervé KK, *et al.* Microbiological and physico-chemical characteristics of cow milk for the extraction of its milk fat for new products production. *SSRG International Journal of Agriculture and Environmental Science.* 2019;6(4):57-64.
7. Goher ME. Chemical studies on the precipitation and dissolution of some chemical elements in Lakes Qarun [PhD thesis]. Egypt: Faculty of Sciences, Al-Azhar University; 2002.
8. Golder D, Chattopadhyay S. Interrelation between physico-chemical characteristics of the tropical lake and their impact on biodiversity of plants. *Journal of Environmental Biology.* 2016;37(6):1281-1289.
9. Kiran BR. Physico-chemical characteristics of fish ponds of Bhadra Project at Karnataka. *RASAYAN Journal of Chemistry.* 2010;3(4):671-676.
10. Kamal D, *et al.* Study on physicochemical properties of water of Mouri River, Khulna, Bangladesh. *Pakistan Journal of Biological Sciences.* 2007;10(5):710-717.
11. Kumar M, Padhy PK. Environmental perspectives of pond ecosystems: Global issues, services and Indian scenarios. *Current World Environment.* 2015;10(3):848-867.
12. Kumari N, Singh SPD. Ecological parameters variation of a fish pond of the village Fatehabad, Muzaffarpur of Bihar. *Recent Life Science Mirror.* 2016;5:12-19.
13. Lodh R, *et al.* Physico-chemical studies of water quality with special reference to lakes of Udaipur City, Tripura, India. *International Journal of Scientific and Research Publications.* 2014;4(6):1-9.
14. Mishra S, Singh AL, Tiwary D. Studies of physico-chemical status of the ponds at Varanasi holy city under anthropogenic influences. *International Journal of Environmental Research and Development.* 2014;4(3):216-268.
15. Mahobe H, Mishra P. Study of physico-chemical characteristics of pond water of Rajnandgaon town, Chhattisgarh. *International Journal of Scientific and Engineering Research.* 2013;4(8):738-748.
16. Mondal NK, Datta J, Banerjee A. Pond alkalinity: A study in Burdwan Municipality, Burdwan, West Bengal, India. *International Journal of Environmental Sciences.* 2011;1(7):1718-1724.
17. Moundiotiya KC, *et al.* A case study of the Jamwa Ramgarh wetland with special reference to physico-chemical properties of water and its environs. *Journal of Environmental Hydrology.* 2004;12:24.
18. Emhanna S, *et al.* Underground pipeline leakage risk evaluation in Ajdabiya City, Libya. *SSRG International Journal of Civil Engineering.* 2022;9(1):7-14.
19. Patel V, Parikh P. Assessment of seasonal variation in water quality of River Mini at Sindhrot, Vadodara. *International Journal of Environmental Sciences.* 2013;3(5):130-145.
20. Patil D, Tijare R. Study on water quality of Gadchiroli Lake. *Pollution Research.* 2001;20(2):257-259.
21. Paul DK, Mukherjee P. A preliminary study of physico-chemical characteristics of a perennial pond. *Journal of Hematology and Ecotoxicology.* 2006;1(1):49-56.
22. Paul DK, Sanyal S. Assessment of seasonal variation of physicochemical characteristics of Sanjay Gandhi Jaivik Udyan Pond, Patna, Bihar, India. *Journal of Patna Science College.* 2017;5:91-107.
23. Prasath BB, *et al.* Seasonal variations in physico-chemical characteristics of pond and groundwater of Tiruchirappalli, India. *Journal of Environmental Biology.* 2013;34(3):529-537.
24. Qureshimatva UF, *et al.* Determination of physico-chemical parameters and water quality index of Chandlodia Lake, Ahmedabad, Gujarat, India. *Journal of Environmental and Analytical Toxicology.* 2015;5(4):1-7.
25. Rylander R, Bonevik H, Rubenowitz E. Magnesium and calcium in drinking water and cardiovascular mortality. *Scandinavian Journal of Work, Environment and Health.* 1991;17(2):91-94.
26. Swarnakar AK, Choubey S. Testing and analysis of pond water in Raipur City, Chhattisgarh, India. *International Journal of Science and Research.* 2016;5(4):1962-1965.
27. Tank SK, Chippa RC. Analysis of water quality of Halena Block in Bharatpur area. *International Journal of Scientific and Research Publications.* 2013;3(3):1-6.
28. Solanki HA, Verma P, Chandawat D. Study of water quality of Hamirsar Lake, Bhuj. *International Journal of Bioscience Reporter.* 2010;8:145-153.
29. Verma PU, Purohit AR, Patel NJ. Pollution status of Chandlodia Lake located in Ahmedabad, Gujarat. *International Journal of Engineering Research and Applications.* 2012;2(4):1600-1606.
30. Wari IA, Subla BA. Physico-chemical features of two shallow Himalayan lakes. *Bulletin of Environmental and Scientific Research.* 1990;8:33-49.